




**FLEXIBLE METAL STRAIGHT SQUEEZE CONNECTORS**

**Straight Squeeze Connectors, Uninsulated Malleable Iron  
N/A**

**B61**



Catalog #: 2106

**APPLICATIONS**

For use in dry locations to bond flexible metal conduit to a box or enclosure  
N/A

**PRODUCT FEATURES**

All malleable iron construction insures mechanical protection for the raceway  
Electro zinc plated for added corrosion protection  
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

**CULUS**

UL Listed E195969

**GENERAL PRODUCT INFORMATION**

Trade Size: 1-1/2 in.

**DRAWING DIMENSIONS**

Dimension A: 2-15/32 in.  
Dimension B: 43/64 in.  
Thread Spec. B: 1-1/2 in. - 11-1/2 NPT  
Dimension C: 1.450 in.  
Dimension D: 1.970 MAX  
Dimension E: 2-27/32 in.

**PACKAGING**

Package Type: Carton  
Ship Carton Qty.: 25  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 65.80  
Ship Carton Length (in.): 9.19  
Ship Carton Width (in.): 8.25  
Ship Carton Height (in.): 6.56  
Ctn Weight (Lbs.): 16.45  
UPC Number: 050169021064  
I2of5: 50050169021069