








Metal Raceway

HBL2400 and HBL2400D Series

Frames and Tools

Devices and Frames	Description	Color	Catalog Number	Description	Color	Catalog Number
	Duplex Receptacle Frame Use this frame in conjunction with duplex receptacles below.	Ivory	HBL24DRK* A: 5.26" (133.60) B: 2.00" (50.80)	Duplex Bracket and Frame Use in low voltage applications with BR106AL and Q106AL frames found on page O-45.	Ivory	HBL24106DRK* A: 6.00" (152.40) B: 2.02" (51.31)
	 			 		
	Receptacle Bracket and Frame Use in low voltage applications with ISFxxAL frames found on page O-45.	Ivory	HBL24106RRK* A: 6.00" (152.40) B: 2.02" (51.31)	Single Receptacle Frame Use this frame in conjunction with single receptacles below.	Ivory	HBL24SRK* A: 3.26" (82.80) B: 2.00" (50.80)
	 			 		
	Duplex Recept. - 15A, 125V Duplex Recept. - 15A, 125V Iso. Grnd Duplex Recept. - 20A, 125V Duplex Recept. - 20A, 125V Iso. Grnd #12 AWG THHN stranded copper wires with 20 in. leads on each end.	Ivory Orange Ivory Orange	PT2RC* PT2RCIG* PT2R* PT2RIG* A: 4.00" (101.60) B: 1.24" (31.50) C: .84" (21.34)	Single Recept. - 15A, 125V Single Recept. - 15A, 125V Iso. Grnd Single Recept. - 20A, 125V Single Recept. - 20A, 125V Iso. Grnd #12 AWG THHN stranded copper wires with 21 in. leads on each end.	Ivory Orange Ivory Orange	PT1RCIV* PT1RCIG* PT1RIV* PT1RIG* A: 2.00" (50.80) B: 1.20" (30.48) C: .87" (22.10)
	 			 		
	Lamp Holder Medium base lamp holder 660W 250V ceramic. Ivory (Cover) White Ceramic (Lamp Holder).	Ivory	HBL2426IV* A: 5.00" (127.00) B: 1.89" (48.01) C: 1.03" (26.16)			
	 					

Note: * Only used on HBL2400 Series Undivided Raceway.

Tools	Description	Catalog Number	Description	Color	Catalog Number
	Cutter Portable cutter for HBL2400/ HBL2400D Series Raceway.	HBL624CUT	Touch-Up Paint Pen	Ivory	HBLIWEP
					
	Cutter Replacement Blade Set	HBL624BCK			
					