



AMT Connectors T&B Catalog Number:

UPC Number:
Status:
Description:

AMTD4146
78378667603
Active

AMT 6 Port Both Sides PVC Connector for Wire Range 4-14 Str.

Features


PVC Insulation eliminates insulation failures and reduces outage costs. Removable port and screw plugs.

Compact design provides space efficiencies.

All cable entry are equipped with an anti-oxidation compound.

General

Style	Both Sides
Insulation	PVC
Material	Aluminum
Wire Range	4-14 Str.
Number of Ports	6
Hex Size	1/8



Dimension Information

Length (inches)	3.07
Width (inches)	1.24
Height (inches)	1.42

Specifications

Temperature Rating	90°C
Voltage Rating	600V

Packaging

T&B Order Multiple	6
Package in Units	6
T&B Sold in UOM	Each
T&B Weight Per UOM	8 lbs. per 100

Notes

UL listed and CSA certified for 600 volts, 90 degrees Celcius.

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com