



220 X 440 - 110/115/120
220 X 440 Primary Volts - 110/115/120 Secondary Volts - 1Ø
Industrial Control Transformer - Finger/Guard

1070



Catalog #: FS21500

PRODUCT FEATURES

- UL listed, CSA certified, and CE Marked
- Voltage Regulation exceeds NEMA requirements
- Constructed out of electrical lamination with precision wound coils
- Touch Protected terminations
- Covered under Acme's 10 year limited warranty

BENEFITS

- Small and lightweight design
- Durable molded plastic terminals
- Fast wire connection terminal

UL STANDARD

UL 506

CSA STANDARD

C22.2 No 66

WARRANTY

Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf

GENERAL PRODUCT INFORMATION

VA:	1500
Primary Voltage:	220 X 440
Secondary Voltage:	110/115/120
Frequency:	50/60 Hz
Max Temperature Rise:	80°C
UL Insulation Class:	130°C

PRODUCT MEASUREMENTS

Height (In./cm):	6.03 (15.3)
Width (In./cm):	6.75 (17.1)
Depth (In./cm):	6.01 (15.3)

CONFIGURATION

Mounting Type:	Floor
Wiring Diagram:	B

PACKAGING

Ship Weight (Lbs/Kg):	38 (17.2)
-----------------------	-----------

COMPLIANCES

UL Standard: UL 506
UL Listed: File E79947
CSA Standard: C22.2 No 66
CSA Listed: LR7357-16
CE: CE Marked
Warranty: Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf