



Distribution Compression Splice

T&B Catalog Number:

AC205

UPC Number:

78378608733

Status:

Active

Description:

Aluminum 9 1/4 inch Full-Tension Distribution Compression Splice for Wire Range: 2/0 (7, 19), Mechanical Dies: BY41, W-245, 635, Hydraulic Dies: B30EA, 245, 635

Features

- Center stop ensures proper conductor positioning.
- External end taper provides conductor stress relief, ease of stringing and corona protection.
- Internal end chamfer enables easy conductor insertion and prevents sharp edge contact with conductor.
- Standards compliant. Meets ANSI C119.4 requirements - withstands 95 percent of conductor rated breaking strength.

General

Style	Full-Tension
Material	Aluminum
Wire Size	2/0 (7, 19)
EEL Classification	9A

Dimension Information

Length (inches)	9 1/4
-----------------	-------

Tooling

Mechanical Tool OD58 Dies	BY41
Mechanical Tool OD58 Crimps Per End	8
Mechanical Tool MD Series Dies	W-245
Mechanical Tool MD Series Crimps Per End	8
Mechanical Tool O-52 Dies	635
Mechanical Tool O-52 Crimps Per End	8
Hydraulic Tool JB12B Dies	B30EA
Hydraulic Tool JB12B Crimps Per End	4
Hydraulic Tool Y Series Dies	245
Hydraulic Tool Y Series Crimps Per End	4
Hydraulic Tool WH Series Dies	635
Hydraulic Tool WH Series Crimps Per End	4

Packaging

Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	28 lbs. per 100

Notes

OD58 Dies are interchangeable with those listed for O-52.

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com