



**Tray and Cord Fittings**  
**T&B Catalog Number:**

**UPC Number:**  
**Status:**  
**Description:**

4-300TC  
 78621071251  
 Active

Tray Cable Connector-TC Series, Aluminum, 3 in. Hub Size, Cable range diameter-2.150-2.700.

**Features**

Precision machined parts, full tapered hub threads, gas tight thread engagement.

**Application**

Provides means for passing TC type cable from cable tray installations into an enclosure or threaded bulkhead.

**General**

Material Aluminum

**Dimension Information**

|                      |             |
|----------------------|-------------|
| Hub Size (inches)    | 3           |
| Dimension A (inches) | 4.69        |
| Dimension B (inches) | 3.86        |
| Cord Range (inches)  | 2.150-2.700 |

**Specifications**

3dmodel Available on Website

**Packaging**

|                    |                |
|--------------------|----------------|
| Package in Units   | 1              |
| T&B Sold in UOM    | Each           |
| T&B Weight Per UOM | 3.94 lbs. Each |

**Notes**

When installed with the two part epoxy in the intended manner the fitting is suitable for the following hazardous locations-Class I, Div.2, Groups C, D.

Suitable for use with sunlight-oil resistant tray cable; suitable for 90&#176; cable, SL Integral Seal.

**Certifications**

RoHS Compliance Yes

**Certifications**



File Nbr:  
 E 82038

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com