



Aluminum Lug
T&B Catalog Number:

ALS19
 78378605084
 Active

UPC Number:
Status:
Description:

Aluminum Two-Hole Lug - Straight Long Barrel, Wire Range 336 30/7, 26/7, 18/1, 397 18/1 ASCR, 336-400 Str., 450-500 Compact, 1/2 Inch Bolt Size, Blind-End, Hydraulic Dies: B80EA, EEI 13A, 655, 1 1/8, 321, 96H, CSA 26

Features

Complete die and crimp information clearly indented on each lug. Install with standard tools and dies.
 NEMA standard mounting holes. Use 1/2 inch mounting hardware for all sizes.
 Prefilled with oxide inhibitor.

General

Style	ALS
Material	Aluminum
Conductor Range - ASCR	336 30/7, 26/7, 18/1, 397 18/1
Conductor Range - Stranded	336-400
Conductor Range - Compact	450-500

Dimension Information

Length (inches)	5 9/16
Width (inches)	1 3/8
T (inches)	9/16
Diameter Min. (inches)	0.743
Diameter Max. (inches)	0.666

Tooling

Hydraulic Dies	B80EA, EEI 13A, 655, 1 1/8, 321, 96H, CSA 26
----------------	--

Packaging

T&B Inner Pack	25
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	35 lbs. per 100

Notes

Available tin-plated (add suffix P to catalog number).

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com