

**Service Entrance Splices****T&B Catalog Number:**

RS403

UPC Number:

78378608656

Status:

I

Description:

Aluminum 6" Service Entrance Compression Splice for Wire Range - End A: 400-336 MCM, End B: 4/0, Die: 5/8

Features

Prefilled with Oxide Inhibitor.

Standards compliant. Meets ANSI C119.4 requirements.

General

Insulation Type	Non-Insulated
Material	Aluminum
Barrel Length	Longer Length
Conductor Range A Str./Sol.	400-336 MCM
Conductor Range B Str./Sol.	4/0

Dimension Information

Length (inches)	7.5
Conductor A Diameter Max.	0.726
Conductor A Diameter Min.	0.666
Conductor B Diameter Max.	0.528

Tooling

Hydraulic Dies	B20AH, 318, 1 5/16
----------------	--------------------

Packaging

Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	101.14 lbs. per 100

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com