

## Russellstoll\*

DuraTite & Ever-Lok Locking Connections T&B Catalog Number:

8418

**UPC Number:** 70891715561

Status: Active

**Description:** 

Heavy Service Ever-Lok 60 Amp, Plug, 3 Pole 4 Wire, 480VAC, 1" Conduit Size

| duit Size         |  |
|-------------------|--|
| Features          |  |
|                   | Molded arc-resisting composition interiors with machined, full-floating, self-aligning contacts.   |
|                   | Safety-polarized interiors that can only be assembled in the correct position.   |
|                   | Automatic locking features makes plug casing mechanically fast to receptacle or connector.   |
|                   | Automatic locking features makes plug casing mechanically fast to receptacle or connector.   |
| Application       |  |
|                   | General Industrial: Lighting Connections, Indoor Welding Stations, Machinery/Tool Connections, Power Distributions Panels, Convenience Power, Battery Charging Equipment   |
|                   | General Industrial: Lighting Connections, Indoor Welding Stations, Machinery/Tool Connections, Power Distributions Panels, Convenience Power, Battery Charging Equipment   |
|                   | Construction: Generator Set Panels, Portable Tools and Equipment, Limited-Life Installations, Portable Lighting Equipment&Itbr>OEMs: Export Machinery, Critical Power Connections, International Indoor Usage, Transportable Equipment |
|                   | Instrumentation: Portable Equipment, Critical Power Connections and Robotics Power, Motor Power Connections, Test Equipment, Laboratory/Test Stations  |
| General           |  |
| Chulo             | Diva   |
| Style<br>Material | Plug  Cast aluminum, corrosion-resistant copper-free alloy   |
| Material_1        | Epoxy powder-coated finish housing   |
| Frequency         | 60 Hz  |
| Amperage          | 60 Amp   |
| Pole/Wire         | 3P/4W  |
| System            | Industrial & Commercial  |
| Specifications    |  |
| Voltage           | 480 Volts AC   |
| Packaging         |  |
|                   | ,  |
| T&B Inner Pack    | 1  |
| Package in Units  | 12   |
| T&B Sold in UOM   | Each   |



| T&B Weight Per UOM             | 3.25 lbs. Each       |
|--------------------------------|----------------------|
| Application Support            |                      |
|                                |                      |
| Overview                       | Available on Website |
| Russellstoll Application Guide | Available on Website |
| Certifications                 |                      |
|                                |                      |
| RoHS Compliance                | No                   |

## For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com