



Split-Bolt
T&B Catalog Number:

4AAW

UPC Number:

78378685510

Status:

Active

Description:

Type AAW Aluminum Split-Bolt Connector with Spacer and Washer for Use on Aluminum, ASCR Conductors. Conductor Range for Equal Main and Tap 2 Sol.-8 Sol.

Features

Bolt, nut, pressure bar and contoured spacer of aluminum alloy. Large contoured spaces provides wide separation.

Nut anodized to prevent thread galling.

General

Style	Type AAW
Wire Type	Aluminum, ASCR
Material	Aluminum
Plating	Electro Tin-Plated
Conductor Range for Equal Main and Tap 2 Sol.-8 Sol.	
Conductor Range Min. Tap with one Max. 8 Sol.	
Main	
Conductor Range For Equal Main and Tap ACSR	4-8

Dimension Information

A (inches)	19/32
B (inches)	0.272
C (inches)	25/32
D (inches)	1 15/32

Packaging

T&B Inner Pack	100
Package in Units	600
T&B Sold in UOM	Each
T&B Weight Per UOM	7 lbs. per 100

Notes

Blackburn Contax recommended when used on aluminum conductor.

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

