



## Compression Pin Terminal T&B Catalog Number:

**UPC Number:** PRS40N  
 78378605048  
**Status:** Active  
**Description:**

Compression Pin Terminal Aluminum, Contax filled for Wire Range 397 18/1, 477 18/1 ASCR, 450-500 MCM, Pigtail: 0.625 x 8, Hydraulic Dies: B20AH, CSA28, EEI 14A, 318, 1064, 1 5/16

### Features

Sleeves are made of highly conductive aluminum.  
 Pigtails are solid copper, tin plated.  
 Prefilled with oxide inhibitor.  
 Install with standard tools and dies.

### General

Style	PKS, PKL, PRS
Material	Aluminum
Conductor Range - ASCR	397 18/1, 477 18/1
Conductor Range - Stranded	450-500 MCM

### Dimension Information

Copper Pigtail Length	0.625
Copper Pigtail Diameter (inches)	8

### Tooling

Hydraulic Dies	B20AH, CSA28, EEI 14A, 318, 1064, 1 5/16
----------------	--

### Packaging

Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	149.5 lbs. per 100

### Certifications

RoHS Compliance	Yes
-----------------	-----

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: techsupport@tnb.com