

# Russellstoll®

## J-Line Interconnection Systems

T&B Catalog Number:

JPS1034H

UPC Number:

70891719079

Status:

Active

Description:

J-Line Plug Watertight/Weathertight With Screw Collar, 100 Amp, Pole , with 1.5" Bushing I.D.



### Features

One-piece interior assemblies interchangeable from regular to reverse service in the field with a screw-driver. Reversed contacts flexibility within any housing.

Wiring space ample for maximum requirements; cable clamps are adjustable for maximum range of cable sizes.

Quick conversion between weathertight flap cover and watertight screw cap assemblies. Flap cover can be rotated and locked in any convenient position.

Quick conversion between weathertight flap cover and watertight screw cap assemblies. Flap cover can be rotated and locked in any convenient position.

### Application

Value alternative to MaxGard® in 3 Pole 4 Wire, 30 to 200 Amp applications with less severe need.

Value alternative to MaxGard in 3 Pole 4 Wire, 30 to 200 Amp applications with less severe need.

### General

Style	Watertight Plug
Material	Cast aluminum, corrosion-resistant copper-free alloy housings and enclosures
Material_1	Epoxy powder coat finish
Material_2	Silver plated contacts
Frequency	60 Hz
Amperage	100 Amp
System	Heavy Industrial & Marine

### Dimension Information

Overall Dimensions Available on Website

### Specifications

Voltage Maximum 600VAC/250VDC

### Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	3.8 lbs. Each

### Application Support

Overview	Available on Website
Russellstoll Application Guide	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)