



## Split-Bolt T&B Catalog Number:

**UPC Number:** 40AAW  
78378685522  
**Status:** Active  
**Description:**

Type AAW Aluminum Split-Bolt Connector with Spacer and Washer for Use on Aluminum, ASCR Conductors. Conductor Range for Equal Main and Tap 4/0 Str.-4 Sol.

### Features

Bolt, nut, pressure bar and contoured spacer of aluminum alloy. Large contoured spaces provides wide separation.

Nut anodized to prevent thread galling.

### General

Style	Type AAW
Wire Type	Aluminum, ASCR
Material	Aluminum
Plating	Electro Tin-Plated
Conductor Range for Equal Main and Tap 4/0 Str.-4 Sol.	
Conductor Range Min. Tap with one Max. 4 Sol.	
Main	
Conductor Range For Equal Main and Tap ACSR	4/0-4

### Dimension Information

A (inches)	1
B (inches)	0.580
C (inches)	1 1/4
D (inches)	2 15/32

### Packaging

T&B Inner Pack	25
Package in Units	150
T&B Sold in UOM	Each
T&B Weight Per UOM	19 lbs. per 100

### Notes

Blackburn Contax recommended when used on aluminum conductor.

### Certifications

RoHS Compliance	Yes
-----------------	-----

### Certifications



File Nbr:  
E9809

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321

