

Flexible Conduits & Fittings T&B Catalog Number:

ALND-M207

UPC Number: 78620994311 **Status:** Active

Description:

Smart Line straight black connector with integral cone seal. Material polyamide 6, thread size - M20 x 1.5.

polyamide 6, thread size - M20 x	1.5.
Application	
	Machine building, installation and construction industries
Characteristics	
	Easy push-in installation
	Easy re-opening with screwdriver
	Space savings due to compact design
	Self-extinguishing, free of halogens and cadmium
	Excellent impact strength
	Fits both conduit profiles - fine (T) and coarse (G)
General	
Material	Polyamide 6
Color	Black
Thread Type	Metric
Suitable for Use With	PMA Smart Line Conduit, PMAFLEX
Dimension Information	Time official Elife Conduit, Time Elex
Fits to Conduit Size (NW)	17
Fits to Conduit Size (metric)	20
Fits to Conduit Size (inches)	1/2
Thread Length (mm)	11.0
Thread Size (Metric)	M20 x 1.5
Technical Information	
Temperature Range-Continuous (Celsius)) -40° C to +105° C
Temperature-Short-Term (Celsius)	+150° C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website
Specifications	
3dmodel	Available on Website
IP Ratings	Available on Website
IP Rating	IP66 stat. / IP54 dyn.
Packaging	
T&B Inner Pack	100
Package in Units	500
T&B Sold in UOM	Each
T&B Weight Per UOM	0.02 lbs. Each
Application Support	
PMA Reference Guide	Available on Website
Conduit Guide-Smart Line	Available on Website
Product Overview-Smart Line Conduits	Available on Website
Product Overview-Smart Line Connectors	
Product Overview-System Supports	Available on Website



Prouduct Overview-PMAFIX Connectors Available on Website

Certifications

RoHS Compliance Yes

Certifications



For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com