

Blackburn°

Automatic Splices T&B Catalog Number:

ATS4

UPC Number: 78378691839

Status: Active

Description:

Autoset Automatic Tension Splice for Wire Range: 4 6/1, 7/1 ASCR, 4 AAC, 4 AAC, Aluminum, Color Code 4 - Orange

AAAC, 4 AAC, Aluminum, C	olor Code 4 - Orange
Features	
	Color-coded end pieces provide for visual identification of maximum conductor size. Color-coded tape further eliminates errors and speeds up installations. Funnel shape swiftly guides conductor into position for insertion.
	Pilot cap envelops strands and guides conductor past serrated jaws and into the center of the splice.
	Die-cast, precision-made jaws provides optimum contact area for a greater range of conductor sizes. Compression spring positions the jaw for positive conductor acceptance.
	High-Strength aluminum alloy tubing covers the connection for superior corrosion protection and long-lasting durability. Tubular center stop automatically determines proper insertion length of both conductors.
General	
Stulo	ATS Autoset
Style Material	Aluminum
	4 6/1, 7/1
Conductor Range - ASCR	4 6/1, 7/1
Conductor Range AAAC Conductor Range AAC	4
Color Code	4 - Orange
Dimension Information	4 · Orange
Length (inches) Packaging	13 3/4
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	43 lbs. per 100
Application Support	
T&B Instruction Sheets	027-365-02-tb2
Certifications	
RoHS Compliance	Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com