

Eaton heavy duty DC disconnect

DCU3064URM

UPC:786685625225

Dimensions:

- **Height:** 11.63 IN
- **Length:** 35.38 IN
- **Width:** 24.46 IN

Weight:70 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** DC disconnect/ungrounded system
- **Amperage Rating:** 200A
- **Application:** Solar
- **Enclosure:** NEMA 3R
- **Enclosure Material:** Painted galvanized steel
- **Fuse Configuration:** Non-fusible
- **Ground:** Ungrounded
- **Main Lug Wire Size:** LC: In 300 MCM-#6 out 300 MCM-#6. SR: in 300 MCM-#6 out 300 MCM-#6. EG: in #4-#14 AWG out 1/0-#14
- **Maximum Voltage:** 600 Vdc
- **Number Of Circuits:** 3
- **Series:** DC Photovoltaic Applications
- **Switch Type:** Heavy-duty
- **System Voltage:** 600 Vdc per pole

Supporting documents:

- [DC disconnects for grounded and ungrounded photovoltaic installations](#)
- [Eatons Volume 15-Solar Inverters and Electrical Balance of System](#)

- [Eaton Specification Sheet - DCU3064URM](#)

Certifications:

- UL 98B
- NEC 690 per UL 1741

Product compliance: No Data

© 2016 Eaton. All rights reserved.