

Two Gang



2FS

2FD

Three Gang



3FS

3FD

FEATURES-SPECIFICATIONS

Applications

- Accommodates wiring devices and provides opening to splice, tap, or pull conductors
- Provide access to conductors for maintenance and future system changes

Features

- Internal grounding screw
- Available single and two gang styles
- Suitable for use in wet locations when used with gasket covers
- For use with FS-style covers see pages F40-F42

Conduit Opening Data

- To specify conduit openings select the letter on these sketches which indicates the position desired. Follow this letter with the symbol indicating the type and size.

Example: 2FS-A2-E2

Material/Finish


Copper-free Aluminum
(less than 4/10 of 1%)

- Electrostatically applied powder coating

FS/FD MULTI GANG BOXES ^①						
SERIES	A	B	C	D	E	H
FSQ	3-3/4"(95)	3-9/16"(90)	1/4"(6)	4-9/16"(116)	2-13/16"(71)	2"(51)
2FS	6-3/16"(157)	3-3/4"(95)	9/32"(7)	4-7/8"(124)	4-15/16"(125)	2"(51)
3FS	6-3/16"(157)	5-3/4"(146)	9/32"(7)	4-7/8"(124)	6-3/4"(125)	2"(51)
FDQ	3-3/4"(95)	3-9/16"(90)	1/4"(6)	4-9/16"(116)	2-13/16"(71)	2-7/8"(73)
2FD	6-3/16"(157)	3-3/4"(95)	9/32"(7)	4-7/8"(124)	4-15/16"(125)	2-7/8"(73)
3FD	6-3/16"(157)	5-3/4"(146)	9/32"(7)	4-7/8"(124)	6-3/4"(125)	2-7/8"(73)

FS/FD/FSQ/FDQ CONDUIT OPENING AND SYMBOL IDENTIFICATION		
FOR CONDUIT SIZE	THREADED SYMBOL NUMBER	UNION ^① SYMBOL NUMBER
1/2"	1	11
3/4"	2	12
1"	3	13
1-1/4"	4	14
1-1/2"	5	15


^①Union hubs are supplied by using a drilled and tapped opening with GUM Series union on 1/2", 3/4", 1", 1-1/4" and 1-1/2" sizes.



Single Gang

Two Gang

Three Gang



KILLARK®