Rittal - The System.

Faster – better – everywhere.

Conductor TerminalsSV 3452.500


Date : May 29, 2018



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Conductor Terminals – SV 3452.500

created: 29.05.2018 build on www.rittal.com/us-en



Product description	
Description:	For connecting round conductors and laminated copper bars.
Material:	Carbon steel
Surface finish:	Zinc-plated, passivated
Note:	Wire end ferrules should be used with fine stranded wire conductors.
Product features	
Suitable for busbars:	Cross-section (thickness): 5 mm
Clamping area for laminated copper bars::	Height: 11 mm Width: 10.5 mm (0.41 ")
Connection for round conductor cross-sections:	16 mm² - 50 mm²
Packaging unit:	15 pc(s).
Weight/packaging unit:	1.02 kg (2.2 lb.)
EAN:	4028177042698
Customs tariff number:	85369010
ETIM 6.0:	EC000001
© Rittal 2018	

ETIM 5.0: EC000001 eCI@ss 8.0/8.1: 27141146 eCI@ss 7.0/7.1: 27141146 eCI@ss 6.0/6.1: 27141146 eCI@ss 5.1/5.1.4: 27370302 Product description (long): SV Conductor connection clamp, 16-50 mm², clamping area WH: 10,5x11 mm, for bar thickness 5 mm Approvals C-UR UR Certificates: EAC Declarations: Declaration of conformity		
eCl@ss 7.0/7.1: 27141146 eCl@ss 6.0/6.1: 27141146 eCl@ss 5.1/5.1.4: 27370302 Product description (long): SV Conductor connection clamp, 16-50 mm², clamping area WH: 10,5x11 mm, for bar thickness 5 mm Approvals Approvals: C-UR UR Certificates: EAC	ETIM 5.0:	EC000001
eCl@ss 6.0/6.1: 27141146 eCl@ss 5.1/5.1.4: 27370302 Product description (long): SV Conductor connection clamp, 16-50 mm², clamping area WH: 10,5x11 mm, for bar thickness 5 mm Approvals C-UR UR Certificates: EAC	eCl@ss 8.0/8.1:	27141146
eCl@ss 5.1/5.1.4: 27370302 Product description (long): SV Conductor connection clamp, 16-50 mm², clamping area WH: 10,5x11 mm, for bar thickness 5 mm Approvals Approvals: C-UR UR Certificates: EAC	eCl@ss 7.0/7.1:	27141146
Product description (long): SV Conductor connection clamp, 16-50 mm², clamping area WH: 10,5x11 mm, for bar thickness 5 mm Approvals C-UR UR Certificates: EAC	eCl@ss 6.0/6.1:	27141146
Approvals Approvals: C-UR UR Certificates: EAC	eCl@ss 5.1/5.1.4:	27370302
Approvals: C-UR UR Certificates: EAC		
Certificates: EAC	Approvals	
	Approvals:	
Declarations: Declaration of conformity	Certificates:	EAC
	Declarations:	Declaration of conformity

© Rittal 2018