

Rittal – The System.

Faster – better – everywhere.

Fuse Holders 61 A to 400 A – SV 9345.400

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Fuse Holders 61 A to 400 A – SV 9345.400

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version: For busbar systems

Material: Polyamide (PA 6)
Fire protection corresponding to UL 94-V0
Contact tracks: Electrolytic copper, silver-plated

Color: Chassis: RAL 7035
Cover: RAL 7035/7001

Note: UL (listed accessory) is met through use of the fuse holder on RiLine busbar systems

Product features

Suitable for busbars: with cross-section height: 5 mm (0.2 ")
with cross-section height: 10 mm (0.39 ")

Number of poles: 3-pole

For bar systems with center-to-center spacing: 60 mm

Dimensions: Height: 328 mm (13 ")
Width: 250 mm (9.8 ")

Type of connection (electrical): Box terminal

Rated operating voltage: 600 V, 3~

Connection for round conductor cross-sections:	AWG 4/0 – MCM 600
Rated operating current min.:	201 A
Rated operating current max.:	400 A
Cable outlet:	Top/bottom
Suitable for fuses:	Fuse type (class): J Fuse standard: UL 4248-8 Ø x length: 54 mm x 181 mm
Packaging unit:	1 pc(s).
Weight/packaging unit:	5.32 kg (11.7 lb.)
EAN:	4028177615670
Customs tariff number:	85365080
ETIM 6.0:	EC001900
ETIM 5.0:	EC001900
eCl@ss 8.0/8.1:	27400613
eCl@ss 7.0/7.1:	27400613
eCl@ss 6.0/6.1:	27400613
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Fuse holder, Class J, 201-400 A, 600 V, 3-pole, (60 mm)
Approvals	
Approvals:	C-UR UL + C-UL UR
Certificates:	EAC