



BURNDY Catalog Number
UPC Number
Description
Status

YGLR29C100
 7818100348355
 2-250 GRD GRID TO 1 IN R
 Active

Web Use
 BURNDY Product Line

Dimensional

Length (in) 2.63
 B Length (in) 0.75
 D - in 0.50
 BB - Length (in) 0.88
 B Length (Fraction) 3/4

General

Product Description High Conductivity Wrought
 Copper Ground Rod Connector, #2
 Str. thru 250 kcmil commercial
 Cu, 91.65 kcmil thru 248.8 kcmil
 Cu weld, 2.63 IN L
Prefilled (Oxide Inhibitor) Y

Other

Type of Oxide Inhibitor Penetrox E

Approvals / Certifications

Rated for Direct Burial Y
UL Listed Y
CSA Certified Y
ROHS Compatible Compliant
UL Recognized N
CULUS N
Industry Standards UL467, IEEE 837

Conductor(s)

Rod Size (Side B) - Range 1 in
Copper Str Size (Side A) - Range 2 AWG-250 kcmil

Physical

Type of Plating Unplated
Plated (Yes or No) N
Product Material Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175