Anchors

Plastic Conical Anchors

- · Designed for use with lightweight fixtures.
- · Recommended for use in concrete, block and brick.
- Recommended for light duty static applications where holding power is not critical.
- · Not recommended for overhead use.
- · Kit includes 100 anchors, 100 screws and one drill bit.
- · Made of engineered plastic.





Plastic Conical Anchor - Data	#8		#10 - #12	
	Tension	Shear	Tension	Shear
	(lbs.)	(lbs.)	(lbs.)	(lbs.)
Nominal Weight Concrete *	110	70	140	90
Hollow Concrete Masonry **	60	45	70	55
Clay Brick Masonry ***	30	50	55	65
Minimum Embedment Depth	7/8"	7/8"	1"	1"

- * Based on concrete compression strength of 4000 psi.
- ** Based on hollow concrete masonry with minimum compression strength of 1500 psi.
- *** Based on clay brick masonry with minimum compression strength of 1500 psi.

Loads contain an applied safety factor of 4.0. For additional loading information contact factory.

UPC/Part Number	Catalog Number	Screw Size	Box Qty.	
Plastic Conical Anchor				
782051 53307	APC-8K	#8 x 1"	100	
782051 53308	APC-10K	#10 x 1"	100	
782051 53309	APC-12K	#12 x 1"	100	