



Steel - Raintight

Images



Application

For maintaining wet locations seal on rated enclosures. Coated Washer installs on outside of 3R rated enclosure. Uncoated washer should be installed inside to maintain raceway continuity. Center reducing washers in middle of knock-out. Listed for use with Wet Location Connectors, or Threaded Rigid Conduit (and IMC) with standard locknuts. Patent Pending

Product Information

Material: Galvanized Steel with EPDM Rubber Coating

Certifications & Codes:

Federal Specification Number: A-A-50553
NEMA Standard: FB-1
UL File Number: E11259, cULus
UL Standard: UL514B
UNSPSC: 39121321

[Download Photo Image](#) [Download Dimensional Image](#)
Dimension A in Inches: 1.05
Dimension B in Inches: 2.34
Dimension C in Inches: 1.38

Catalog ID: 1065-RT

UPC Number: 78174714065

Description: Mighty-Seal® 1-1/4" to 3/4" Raintight Reducing Washers. Product contains one coated and one uncoated galvanized steel reducing washer. Maintains Raceway Integrity. Sunlight Resistant. Suitable for Use in Wet Locations.

Application: For maintaining wet locations seal on rated enclosures. Coated Washer installs on outside of 3R rated enclosure. Uncoated washer should be installed inside to maintain raceway continuity. Center reducing washers in middle of knock-out. Listed for use with Wet Location Connectors, or Threaded Rigid Conduit (and IMC) with standard locknuts. Patent Pending

Trade Size: 1-1/4" - 3/4"

Std Pkg Qty: 200

Unit Qty: 20