Rittal - The System.

Faster – better – everywhere.

Captive nut – TS 8800.340

Date : May 24, 2018



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Captive nut – TS 8800.340

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description:

The nuts are inserted from the same side as screw-fastening takes place. This allows fastening points at the same height and width across corners. The spring retainer also provides for electrical connection in the system punchings.

Product features

Installation options:

On enclosures and rails with rectangular hole profile $12.5 \times 10.5 \text{ mm}$ Vertical TS, SE enclosure section via adapter rails for PS compatibility

TS horizontal, direct

On the horizontal SE enclosure section, bottom, direct

On the horizontal SE enclosure section, top (in the depth only), direct

Punched rails 23 x 23 mm Mounting chassis 23 x 73 mm Mounting chassis 45 x 88 mm System chassis 23 x 73 mm

Thread:

Type: M6

Packaging unit:

50 pc(s).

Weight/packaging unit:

0.15 kg (0.3 lb.)

EAN:

4028177231849

Customs tariff number:

73181692

ETIM 6.0:

EC002358

ETIM 5.0:

EC002358

© Rittal 2018

1

e CI@ss 8.0/8.1:	23110815
e CI@ss 7.0/7.1:	27189234
eCl@ss 6.0/6.1:	27189234
eCl@ss 5.1/5.1.4:	27189234
Product description (long):	TS Captive nut, for thread M6, for insertion from the front

© Rittal 2018 2