



## **DOE 2016 Efficient Transformer**

V48M47T3016CU

UPC:786680192661

**Dimensions:** 

Height: 36.88 INLength: 21.13 INWidth: 24.88 IN

Weight: 1.1 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

**Specifications:** 

Coil Material: Copper
Efficiency: DOE2016
Enclosure: NEMA 2

• Frame: 940

• Frequency Rating: 60 Hz

Insulation: 220CKva Rating: 30 kVAPhase: Three-phase

Primary Voltage: 480 DELTA
Secondary Voltage: 480Y/277
Sound Level: NEMA ST-20
Tap Size: 2 at +2.5%, 4 at -2.5%
Temperature Rating: 150°C rise

• Voltage Rating: 480-480Y/277V

• Weathershield: WS58

**Supporting documents:** 

• Eaton Specification Sheet - V48M47T3016CU

Certifications: No Data



P	ro	duc	t co	mnli	iance:	No	Data
	ı	uuc		шрп	iaiice.	INO	Data

© 2016 Eaton. All rights reserved.