## Single Expansion Anchors

- For use in concrete, block, brick or stone.
- · Recommended for floor and wall attachments.
- · Not recommended for overhead applications.
- Internally threaded anchor for easy removability and service work.
- · Made of Zamac Alloy material.



Single Expansion - Data	1/4"	3/8"	1/2"	5/8"
ANSI Drill Bit Size (in.)	1/2	3/4	<sup>7</sup> /8	1
Max. Tightening Torque (ft-lbs)	5	10	20	30
Thread Size (UNC)	1/4"-20	<sup>3</sup> /8"-16	<sup>1</sup> /2"-13	<sup>5</sup> /8"-11
Thread Length In Cone (in.)	<sup>5</sup> /16	<sup>5</sup> /16	<sup>7</sup> /16	5/8
Min. Embedment Depth (in.)	1 <sup>3</sup> /8	1 <sup>5</sup> /8	21/2	23/4
Load Capacity Tension (lbs) *	100	510	610	925
Load Capacity Shear (lbs) *	140	805	1000	1710

<sup>\*</sup> Based on concrete compression strength of 4000 psi using applied safety factor of 4.0. For additional loading information contact factory.

UPC/Part Number	Catalog Number	Rod Size	Anchor Length	Box Qty.			
Single Expansion Anchor							
78101103245	ASE-25	1/4"	1 <sup>5</sup> /16"	50			
78101103247	ASE-37	3/8"	11/2"	50			
78101103248	ASE-50	1/2"	2 <sup>1</sup> /16"	25			
78101103249	ASE-62	5/8"	2 <sup>5</sup> /8"	25			

<sup>‡</sup> Not ICC-ES listed