

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted enclosures EL, 3-part with mounting plate and profile rails, static installation – EL 2271.605

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part with mounting plate and profile rails, static installation – EL 2271.605

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Version: with mounting plate and profile rails, static installation

Description: Wall-mounted enclosure with hinged door provides optimum accessibility.

Material: Wall and hinged part: Carbon steel, 1.5 mm
Viewing window: Single-pane safety glass, 3 mm

Surface finish: Powder-coated

Color: Wall and hinged part: RAL 7035
Viewing door: RAL 7035/7015 (slate gray)

**Protection category
IP to IEC 60 529:** IP 55

Supply includes: Wall section with flange (gland) plate, top and bottom, and mounting plate (supplied loose).
Hinged part with 25 mm pitch pattern in the front and rear frame, two 19" profile angles at the front, fixed in place
Designer viewing door
1 enclosure key double bit no. 5
Comfort handle and 2-point locking
Security lock 3524 E

Base material: Carbon steel

Product features

Dimensions: Height: 1012 mm (40 ")
Height units: 21 U (21 U)

Width: 600 mm (24 ")
Depth: 473 mm (19 ")

Depth hinged part:	316 mm (12 ")
Installation depth:	420 mm (17 ")
Clearances:	Clearance height: 949 mm (37 ") Clearance width: 502 mm (20 ")
Mounting plate:	Height: 965 mm (38 ") Width: 485 mm (19 ")
Wall section:	Depth: 135 mm (5.3 ")
Load capacity:	Hinged part, static (max.): 750 N (750 N)
Packaging unit:	1 pc(s).
Weight/packaging unit:	56 kg (123.5 lb.)
EAN:	4028177324435
Customs tariff number:	94032080
ETIM 6.0:	EC002500
ETIM 5.0:	EC002500
eCl@ss 8.0/8.1:	27180208
eCl@ss 7.0/7.1:	27180208
eCl@ss 6.0/6.1:	27180208
eCl@ss 5.1/5.1.4:	27180204
Product description (long):	EL Wall-mounted enclosures, 3-part, 21 U, WHD: 600x1012x473 mm, Protection category: IP 55, Designer glazed door

Approvals

Approvals:	Germanischer Lloyd Lloyds Register of Shipping UL + C-UL
Certificates:	EAC Protection category

