

Rittal – The System.

Faster – better – everywhere.

Enclosure Light – SZ 9968.112

Date : May 25, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Enclosure Light – SZ 9968.112

created: 25.05.2018 build on www.rittal.com/us-en



Product description

Benefits: Designed for quick and easy installation
External terminal block allows no need to disassemble the light to make electrical connections
Available in 15 or 18 watt rating, they can be used with or without the Rittal door switch.
Equipped with interference suppression capacitor or a RFI filter, they also come with or without a lamp shade or 115 V U.S. style receptacle.

Material: Lamp holder: polycarbonate
Switch: polyester and polycarbonate
Terminal block: nylon

Color: RAL 7044

Supply includes: Fasteners

Product features

Dimensions: Height: 110 mm (4.3 ")
Width: 620 mm (24 ")
Depth: 45 mm (1.8 ")

Rated operating voltage: 120 V, 60 Hz

Equipment (electrical): Light (bulb): Cool white fluorescent
Switch (type): On/off rocker switch

Luminous flux: 1170 lm

Connection options: L1, N, GND

Light – installation type:	Screw fastening
Light – mounting option:	TS vertical profile, direct TS roof frame (horizontal profile), direct
Packaging unit:	1 pc(s).
Weight/packaging unit:	2.3 kg (5.1 lb.)
EAN:	19131