

Insulated Rail Signal Bondstrand – SBS8LINSUL



- Highly flexible and resistant to vibration fatigue
- Allows mechanical or compressed types of connections as well as ERICO CADWELD welded connections
- Insulation manufactured from 600 volt-rated PVC
- Two insulation thicknesses available: 4/64" (0.063", 1.6 mm) and 6/64" (0.094", 2.4 mm)
- Meets or exceeds recommendations and design criteria described in AREMA® Manual Parts 8.1.20, 8.1.25, 8.1.30, 8.1.32 and 10.3.12

Part Number	SBS8LINSUL
Material	Cadmium Bronze Polyvinylchloride
Finish	Bare
Conductor Type	AREMA® S-8
Number of Wires	133
Color	Black
Conductor Size	3/16" Bondstrand
Insulation Thickness	0.063"
Length	500'
Standard Packaging Quantity	500'
UPC	78285667116

AREMA is a registered trademark of American Railway Engineering and Maintenance-of-Way Association, Inc.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.