



## **Fast-Acting Fuse**

**ABC-1/2-R** 

UPC:051712646130

**Dimensions:** 

Height: 1.25 INLength: .25 INWidth: .25 IN

Weight: .007 LB

Notes: Ceramic body allows for higher amp/volt

rating combinations.

Warranties: No Data

**Specifications:** 

• Type: Electronic

• Application: Electronic circuits

Amperage Rating: 1/2A

• Voltage Rating: 250 Vac, 125 Vdc, 32 Vac

(self certified)

• Interrupt Rating: 35 AIC at 250 Vac, 10 kAIC

at 125 Vac/dc

• Fuse Indicator: Non Indicating

Packaging Type: Standard

• Response Time: 4 hr minimum at 100%, 60

min maximum at 135%, 120 s maximum at

200%

Voltage Drop: Typical: .41 mV

• Melting (L2T): Typical pre-arc: .039

• Diameter: .25 IN

• Material: Ceramic tube, nickel-plated brass

endcaps

• Connection: Ferrule end X ferrule end

• Resistance: Typical DC cold: .587 ohms

**Supporting documents:** 

• ABC 1/2A BUSS FA 5-IN BOX -R

Certifications: No Data



## **Product compliance:**

- CE Marked
- RoHS Compliant

\_\_\_\_\_\_

© 2016 Eaton. All rights reserved.