McGill™ Fluorescent Industrial Extension Lights

NEC/CEC: Listed for Ordinary (Unclassified) Locations NEC: Meets OSHA requirements

Applications

 Compact, lightweight with hinged hooks, these fluorescent extension lights were designed to carry and use virtually anywhere.

Features

- · Ideal for use in confined areas.
- Emanates soft, glare-free light.
- Safe and durable, these lamps remain cool to the touch.
- Outer tube protects 15, 8, or 4 Watt lamps.
- Durable, heavy-duty construction throughout.
- Low energy, long-life.
- No exposed metal parts.

Standard Materials

· Impact resistant plastic

NEC/CEC Certification and Compliances

UL Listed: E59071

• UL Standard: 153

CSA Certified: LL89639CSA Standard: C22.2 No. 12





5330-0818

5330-1525

15 Watt Extension Lights

	Catalog Number	
	with 7.6 m (25 ft) Cord	with 15.2 m (50 ft) Cord
15 Watt lamp 54.1 mm (2.13 in) dia., 571.5 mm (22.5 in) length, with SJTO yellow cord — 18/3 from 3 prong plug to ballast, 18/2 to lamp. No. F15T8/CW bulb and FS-2 starter furnished	5330-1525	5330-1550
15 Watt lamp 54.1 mm (2.13 in) dia., 571.5 mm (22.5 in) length, with SJTW yellow cord — 16/3 from 3 prong plug to ballast, 18/2 to lamp. No. F15T8/CW bulb and FS-2 starter furnished	5332-1525 ①	-

4 and 8 Watt Extension Lights

	Catalog Number — 18/2–SJTO Cord		
	with 4.6 m (15 ft)	with 6.7 m (22 ft)	with 7.6 m (25 ft)
4 Watt, F4T5/CW; 279.4 mm (11 in) overall length	5330-0411	5330-0418	_
8 Watt, F8T5/CW; 431.8 mm (17 in) overall length	5330-0811	5330-0818	_
8 Watt, F8T5/CW; 431.8 mm (17 in) overall length	_	5332-0818 ①	5332-0825 ①

Accessories and Replacement Parts

	Catalog Number
Plastic shield for 5330-0411 and 5330-0418	_
Hook only for 5330-0411, -0418, -0811, and -0818	5330-0401
Plastic shield for 5330-0811 and 5330-0818	5330-0800
Plastic shield for 5330-1525	5330-1500
Hooks, plastic, set of two (2) for 5330-1525	5330-1501

① Certified to meet the Canadian Electrical Code (CEC) only.

