

# Flexible Jumper for Fence and Gate Grounding – FJ2G24



- Used to bond gates, switch operating handles and any other item where movement or vibration requires a flexible grounding jumper
- Multi-stranded insulated ropelay conductor provides flexibility and strand protection
- Swaged ends of jumper allow larger conductor to fit in the same mold as concentric conductor
- Connections are made with ERICO CADWELD exothermic connections using the same mold required for other fence post connections

Part Number	FJ2G24
Material	Copper Polyethylene Rubber
Cable Code	2G
Conductor Size	2/0 Stranded
Cable Length	24"
Standard Packaging Quantity	1 pc
UPC	78285632294

Conductor Size	Pipe Size	ERICO CADWELD Mold Part Number	Welding Material Size
#2 Sol	1 1/2" - 4"	VBC1TV3C	65
#2 Sol	4" - 6"	VBC2GV5C	90
2/0 Str	1 1/4" - 3 1/2"	VBC2GV3C	115
2/0 Str	4" - 6"	VBC2GV5C	115
4/0 Str	1 1/4" - 3 1/2"	VBC2QV3C	115
4/0 Str	4" - 6"	VBC2QV5C	115

## WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.