

Rittal – The System.

Faster – better – everywhere.

Rack-mounted fans for 482.6 mm (19") Air throughput 320 - 480 m³/h – SK 3341.115

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Rack-mounted fans for 482.6 mm (19") Air throughput 320 - 480 m³/h – SK 3341.115

created: 24.05.2018 build on www.rittal.com/us-en



Product description	
Supply includes:	Wired unit ready for connection Incl. terminal strip and assembly components
Product features	
Total cooling output/number of fan modules required:	
Air throughput (unimpeded air flow):	480 m³/h (282.5 cfm)
Rated operating voltage:	115 V, 1~, 50 Hz/60 Hz
Dimensions:	Height: 44 mm (1.7 ") Width: 482.6 mm (19 ") Depth: 200 mm (7.9 ")
Distance between fan axes:	85 mm (3.3 ")
Temperature range:	Operation (environment): -10°C...+55°C
Rated current (max.):	At 50 Hz: 0.69 A At 60 Hz: 0.69 A
Miniature circuit-breaker/fuse:	6 A
Noise pressure level:	At 50 Hz: 52 dB(A)

Number of fans:	3
Packaging unit:	1 pc(s).
Weight/packaging unit:	2 kg (4.4 lb.)
EAN:	4028177041479
Customs tariff number:	84145915
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705
Product description (long):	SK rack-mounted fan, for 482.6 mm (19"), 480 m³/h, 115 V, 1~, 50/60 Hz, WHD: 482.6 x 44 x 200 mm
Approvals	
Approvals:	Approval overview UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity