Midget Twist-Lock® Devices 15A, 125/250V AC, 3 Pole, 3 Wire Non-Grounding Flanged Inlet

Features

- Stainless Steel mounting flange
- High heat resistant phenolic base

Ordering Information

inlet.	Description Stainless steel flanged inlet.	Terminals Exposed	UPC 783585237442	Catalog Number HBL7486
--------	--	----------------------	---------------------	---------------------------

Listings

Listed to UL 498 Certified to CSA C22.2 No.42

Specifications


Flange	Stainless Steel
Base	Phenolic
Blades	Brass
Terminal Screws	#5-40 Brass

Performance

Electrical Current Interrupting Dielectric Voltage	Certified for current interrupting at full rated current Withstands 2,000V minimum
Mechanical Terminal Accommodation	#18 AWG - #14 AWG solid or stranded copper wire only.
Terminal Identification	Terminals identified in accordance with UL 498
Environmental Flammability Moisture Resistance Operating Temperatures	HB or better per UL94/CSA 22.2 No.0.17 IP20 Suitability Maximum Continuous 75°C; Minimum -40°C (w/o impact)







Accessories

Valise® Connector	HBL7484V	
Connector	HBL7484	
Angled Connector	HBL7433	

Resources

Customer Use Drawing	
eCatalog	

