



DOE 2016 Efficient Transformer

V48M28F4916CU

UPC:786680192265

Dimensions:

Height: 51 INLength: 31.5 INWidth: 34.5 IN

Weight: 1.1 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

Coil Material: CopperEfficiency: DOE2016Enclosure: NEMA 2

• Frame: 943

• Frequency Rating: 60 Hz

Insulation: 220CKva Rating: 150 kVAPhase: Three-phase

Primary Voltage: 480 DELTA
Secondary Voltage: 208Y/120
Sound Level: NEMA ST-20
Tap Size: 2 at +2.5%, 4 at -2.5%

Tap Size: 2 at +2.5%, 4 at -2.5%
 Temperature Rating: 115°C rise
 Voltage Rating: 480-208Y/120V

Weathershield: WS60Wiring Connection: 280B

Supporting documents:

Eaton Specification Sheet - V48M28F4916CU

Certifications: No Data



P	ro	du	ct	COI	nn	lian	ce:	Nο	Data
	10	u	UL	COI	IIP.	IIGI	UC.	1 40	Data

© 2016 Eaton. All rights reserved.