




# Beam Fasteners With Anchor Straps



- Suspends threaded rod from beam flanges.
- 8" anchor straps are provided for <sup>1</sup>/<sub>8</sub>" to <sup>1</sup>/<sub>4</sub>" thick flanges.
- 13" anchor straps are provided for <sup>5</sup>/16" to <sup>3</sup>/4" thick flanges.



#### Static Load Capacity 75 Lbs.



| UPC/Part<br>Number | Catalog<br>Number | Stud<br>Size                           | Flange<br>Thickness                  | Box<br>Qty. |
|--------------------|-------------------|--|--------------------------------------|-------------|
| 78101104942        | BU-2-4-S-AS       | <sup>1</sup> /4"-20 x <sup>3</sup> /8" | <sup>1</sup> /8" - <sup>1</sup> /4"  | 50          |
| 78101104943        | BU-5-8-S-AS       | <sup>1</sup> /4"-20 x <sup>3</sup> /8" | <sup>5</sup> /16" - <sup>1</sup> /2" | 50          |
| 78101104944        | BU-9-12-S-AS      | <sup>1</sup> /4"-20 x <sup>3</sup> /8" | 9/16" - 3/4"                         | 50          |



Static Load Capacity 160 Lbs.



| UPC/Part<br>Number | Catalog<br>Number | Threaded<br>Rod Size | Flange<br>Thickness                  | Box<br>Qty. |
|--------------------|-------------------|----------------------|--------------------------------------|-------------|
| 78101104948        | BH4-E-2-4-AS      | 1/4"-20              | 1/8" - 1/4"                          | 50          |
| 78101104949        | BH4-E-5-8-AS      | 1/4"-20              | <sup>5</sup> /16" - <sup>1</sup> /2" | 50          |
| 78101104950        | BH4-E-9-12-AS     | <sup>1</sup> /4"-20  | 9/16" - 3/4"                         | 50          |
| 78101104951        | BH6-E-2-4-AS      | <sup>3</sup> /8"-16  | 1/8" - 1/4"                          | 50          |
| 78101104952        | BH6-E-5-8-AS      | <sup>3</sup> /8"-16  | <sup>5</sup> /16" - <sup>1</sup> /2" | 50          |
| 78101104953        | BH6-E-9-12-AS     | <sup>3</sup> /8"-16  | 9/16" - 3/4"                         | 50          |

Read safety/installation instruction sheets in packages before use. These products are designed for positioning only. No load rating.





## **Conduit To Beam Fasteners With Anchor Straps**



- Anchor strap provides secure attachment to beam flanges.
- Unique Guide-Rite™ Fastener provides for fast and easy installation.
- 8" anchor straps are provided for 1/8" to 1/4" thick flanges.
- 13" anchor straps are provided for 5/16" to 3/4" thick flanges.





### Static Load Capacity 75 Lbs.

| UPC/Part<br>Number | Catalog<br>Number | Conduit<br>Size | Flange<br>Thickness                  | Box<br>Qty. |
|--------------------|-------------------|-----------------|--------------------------------------|-------------|
| 78101104966        | BG-8-12-U-2-4-AS  | 1/2", 3/4"      | 1/8" - 1/4"                          | 50          |
| 78101104967        | BG-8-12-U-5-8-AS  | 1/2", 3/4"      | <sup>5</sup> /16" - <sup>1</sup> /2" | 50          |
| 78101104968        | BG-8-12-U-9-12-AS | 1/2", 3/4"      | 9/16" - 3/4"                         | 50          |
| 78101104969        | BG-16-U-2-4-AS    | 1"              | 1/8" - 1/4"                          | 50          |
| 78101104970        | BG-16-U-5-8-AS    | 1"              | <sup>5</sup> /16" - <sup>1</sup> /2" | 50          |
| 78101104971        | BG-16-U-9-12-AS   | 1"              | 9/16" - 3/4"                         | 50          |





## Static Load Capacity

25 Lbs.

| UPC/Part<br>Number | Catalog<br>Number | Conduit<br>Size | Flange<br>Thickness                  | Box<br>Qty. |
|--------------------|-------------------|-----------------|--------------------------------------|-------------|
| 78101104972        | BG-8-12-E-2-4-AS  | 1/2", 3/4"      | 1/8" - 1/4"                          | 50          |
| 78101104973        | BG-8-12-E-5-8-AS  | 1/2", 3/4"      | <sup>5</sup> /16" - <sup>1</sup> /2" | 50          |
| 78101104974        | BG-8-12-E-9-12-AS | 1/2", 3/4"      | 9/16" - 3/4"                         | 50          |
| 78101104975        | BG-16-E-2-4-AS    | 1"              | 1/8" - 1/4"                          | 50          |
| 78101104976        | BG-16-E-5-8-AS    | 1"              | <sup>5</sup> /16" - <sup>1</sup> /2" | 50          |
| 78101104977        | BG-16-E-9-12-AS   | 1"              | 9/16" - 3/4"                         | 50          |

Read safety/installation instruction sheets in packages before use. These products are designed for positioning only. No load rating.