



Coaxial Surge Protector – CSP1NB90



- Simple plug-in installation
- Supplied with mounting bracket and flying lead ground
- Low insertion and return loss
- Wide operating frequency spectrum



Part Number	CSP1NB90
Max Discharge Current (I _{max}), Per Mode	20 kA 8/20 μs
Frequency	0 – 3 GHz
Capacitance	1.5 pF
Insulation Resistance	10 GΩ
Impulse Life	400 @ 500 A 10/1000 μs
Enclosure Material	Metal
Enclosure Rating	IP 20 NEMA®-1
Temperature	-40 to 194 °F
Connection Type	N-Type, Female/Female
Spark-Over Voltage @ 100 V/μs	450 V
Spark-Over Voltage @ 100 V/s	72 – 108 V
Depth (D)	1"
Height (H)	0.984"
Width (W)	0.984"
Unit Weight	0.294 lb
Certifications	CE UL
Standard Packaging Quantity	1 pc
UPC	78285669072
EAN-13	8711893105582

NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.