

Issue Date: 10/29/2012 Page: 1 of 2 PSS-K655YDR File:

15/25kV

600A Deadbreak Insulating Cap

w/o Test Point

K655YDR





Features:

- Fully rated 15/25kV, 600 Amp Deadbreak Insulating Cap
- Fully shielded, fully submersible molded rubber housing
- 100% peroxide-cured construction includes insulation and conductive EPDM materials
- Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state

K655YDR **Insulating Cap**

Applications:

The Elastimold® K655YDR insulated cap is designed to insulate, shield, and water seal 15/25kV, 600 Amp bus bar end interfaces of a K6561-Bus, K656CY-Bus, or a K656CH-Bus. Units come standard with a bail for assembly and easy installation.

Ratings:

Meets ANSI/IEEE Standard 386, Latest Revision

For 15kV Voltage Class:

8.3kV Max Phase-to-Ground - Operating Voltage 14.4kV Max Phase-to-Phase

95kV BIL - Impulse Withstand (1.2 x 50

microsecond wave)

34kV AC - One minute withstand

53kV DC – 15 minutes withstand

11kV AC - Corona Extinction @ 3pC sensitivity

600 Amp - Continuous

25kA Sym - 10 Cycles Momentary

For 25kV Voltage Class:

16.2kV Max Phase-to-Ground - Operating Voltage

28kV Max Phase-to-Phase

140kV BIL - Impulse Withstand (1.2 x 50

microsecond wave)

45kV AC - One minute withstand 84kV DC - 15 minutes withstand

21.5kV AC - Corona Extinction @ 3pC sensitivity

600 Amp - Continuous

25kA Sym – 10 Cycles Momentary





⟨•elastimold Product Specifications


Issue Date: 10/29/2012 Page: 2 of 2 PSS-K655YDR File:


15/25kV

600A Deadbreak Insulating Cap

w/o Test Point

K655YDR





Ordering Instructions:

To order 15/25kV, 600A insulating cap, specify K655YDR.

Each kit contains the following:

1	Insulating Cap	K655YDR
1	Tube, lubricant	82-08
1	Installation Instruction	IS-0501
1	Bail Assembly	650BA

