

Rittal – The System.

Faster – better – everywhere.

Glazed Door for TS, TS IT, SE – TS 8610.825

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Glazed Door for TS, TS IT, SE – TS 8610.825

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Description:	Instead of a sheet steel door or rear panel.
Material:	Frame: Extruded aluminum section Corner pieces: Die-cast zinc Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Color:	Frame: RAL 7035 Corner pieces: RAL 7035 Viewing window (printed mask on the inside): RAL 9005
Protection category IP to IEC 60 529:	IP 55
Mounting tip:	When mounting instead of the rear panel, the lock components are required
Supply includes:	Glazed door frame with safety glass Locking rod with double-bit insert 180° hinges (4 pcs)

Product features

Suitable for:	Enclosure type: TS Enclosure type: TS IT Enclosure type: SE Height: 2200 mm (87 ") Width: 800 mm (31 ")
Viewing area:	Height: 2040 mm (80 ") Width: 660 mm (26 ")

Packaging unit:	1 pc(s).
Weight/packaging unit:	20 kg (44.1 lb.)
EAN:	4028177693876
Customs tariff number:	94039010
ETIM 6.0:	EC000747
ETIM 5.0:	EC000747
eCl@ss 8.0/8.1:	27182204
eCl@ss 7.0/7.1:	27182290
eCl@ss 6.0/6.1:	27182290
eCl@ss 5.1/5.1.4:	27182201
Product description (long):	TS Glazed door, for TS, TS IT, SE, for WH: 800x2200 mm
Approvals	
Certificates:	EAC