

r	ΛI.	\frown	т		9	-
	v	\smile		_	$\mathbf{-}$	_

1. DIMENSIONS ARE INCHES ± .02 [mm] ± .5

2. RATING: 600V 400 AMP

3. UL/c-UL ENCLOSURE TYPES 3R, 4X, 12, SEE INSTRUCTION SHEET

HUBBELL CAT. NO.	COLOR
HBLPTBK	BLACK
HBLPTW	WHITE
HBLPTGN	GREEN
HBLPTBR	RED
HBLPTBL	BLUE
HBLPTO	ORANGE
HBLPTBN	BROWN
HBLPTY	YELLOW

		LIS	ST OF PARTS			_	
	DESC	RIPTION	MATERIAL		FINISH	SEE TABLE	
HOUSING		TPE		SEE TABLE	<u>o</u> <u>s</u>		
FEN		CONTACT	BRASS				
N/14	RIVE	ET ONTACT	BRASS	_		'''	
1017	ALL CC	DNIACI				│	
						TABLE	
				_		- m - ≥	
				_		- Ē	
				_		-	
						REPAIRABLE [
4	600V	SED NOTE 2 AC/250VDC DCN 23410	TO 600V	RGP	11/01/17	NON-REP	
3	CHAN 4.73.	LE REVIEW NGE DIM. FR CHANGED N DCN 20659 (ROM 4.65 TO MARKINGS	CAC	08/15/14	PAIRABLE	
2	& Ø :	VE ∅ 1.06 1.22 [30.9 ∴02 & ±.5 GED NOTE 3	P] TO NOTE 1	TWB	12/15/04		
1			34 TwB R DCN 10992	TWB	6/25/03	₪	
SYM		REVISION	ONS	APP	DATE		
THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE TITLE							
			GLE POL			M-8931	
			ALLING T			(1)	
		FEMA	ALE/MALE	Ξ/ M /	ALE	__\	
			WIRING D	 EVICE	-KELLEMS	† ~	
OTHERWISE SPECIFIED HUBBELL INCORPORATED							
	CTIONS	± 1/64	BRID	GEPOF	RT, CT		
	IMALS	± 005	DR. BY MJ	MA	PP. BY TWB		
DEC			1	0	CALE 1:1	1	
DEC	ÉS	± 2°	TR. BY CHK'D BY TW	_	CALE 1:1 ATE 6/11/03	4	