


## Grounding - Steel

### Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 2.18  
Dimension B in Inches: 3.65  
Dimension C in Inches: 0.73  
Dimension D in Inches: 2.27  
Dimension E in Inches: 3.37

### Application

Used in situations where wires have already been pulled through Rigid/IMC conduit, and an insulated Grounding bushing is required. Grounding lug, aluminum alloy 6061-T6. Rated 150 Degree C. cULus listed. Patented

### Product Information

Material: Steel  
Finish: Zinc Plated, Grounding Lug, Tin Electro-Plate

### Certifications & Codes:

Federal Specification Number: A-A-50553  
NEMA Standard: FB-1  
UL File Number: E20412  
UL Standard: UL-514B  
UNSPSC: 39121312

**Catalog ID:** SGBS-38740

**UPC Number:** 78174723875

**Description:** Split Bushing, Insulated, Grounding, Steel, Size 2-1/2 Inch

**Application:** Used in situations where wires have already been pulled through Rigid/IMC conduit, and an insulated Grounding bushing is required. Grounding lug, aluminum alloy 6061-T6. Rated 150 Degree C. cULus listed. Patented

**Trade Size:** 2-1/2"

**Std Pkg Qty:** 25

**Unit Qty:** -