

Kellems® Wire Management Products  
PG and Metric Threaded Deluxe Cord Grips  
Deluxe Cord Grips

**HUBBELL**

**Features**

- Aluminum Fitting
- Stainless steel mesh is corrosion resistant
- Neoprene bushing is oil and watertight

**Ordering Information**

Description	Hub Size	UPC	Catalog Number
Straight Metric Male Thread, Liquidtight	M32	783585327730	074M32021

**Listings**

UL Listed  
CSA Certified


**Specifications**

Strand	Stainless Steel
Body	Aluminum
Nut	Aluminum
Bushings	Neoprene

**Performance**

**Environmental**

Flammability	UL 94HB (Strand grip), UL 94V-2 (Fitting)
Hazardous Locations	Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C
Operating Temperatures	-30°F to +240°F (-34°C to +115°C)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting



**Online Resources**

Customer Use Drawing  
eCatalog  
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.