




**PART NUMBER:** 60000  
**DESCRIPTION:** 18/2 STRANDED FLAT SPT-1 CABLE  
**CONSTRUCTION:** This cable consists of two bare copper conductors (one bare copper and one tinned copper with clear insulation) laid flat with an integral insulation and jacket.  
**APPROVALS:** UL Standard 62, NEC Article 400, CSA 22.2 No. 49.

**Construction Parameters:**

Conductor	18 AWG Bare Copper (Bare and Tinned with Clear Insulation)
Stranding	41/34
Insulation Material	PVC
Insulation Thickness	0.033" Nom.
Insulated Conductor Dimensions	0.112" x 0.210" Nom.
Number of Conductors	2
Approximate Cable Weight	20.9 Lbs/1M' Nom.
Flame Rating	UL/CSA Horizontal Flame Test



**Electrical Properties:**

Temperature Rating	-20°C to 60°C
Rated Voltage	300 V RMS Max.
Current Per Conductor	10 Amps Max
Capacitance Between Conductors @ 1 KHz	33 pF/ft Nom.
DC Resistance per Conductor @ 20°C	6 Ohms/1M' Nom.

Insulation/Jacket Color	Brown, White, Black, Clear, Gold, Silver (Other colors available - consult factory)
Polarity indication	One side of cable is ribbed (this is also the tinned copper side with clear insulation)
Legend (Indent Print)	18 AWG (.82mm2) 2/C E46194 (UL) SPT-1 60C 300V -- 156016 CSA SPT-1 60C 300V FT1
(Inkjet Print - Clear, Gold, Silver)	18 AWG (.82mm2) 2/C E46194 (UL) SPT-1 60C 300V

This product complies with European Directive 2011/65/EU (RoHS-2)  
 On special orders, the customer will accept all mil lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: August 7, 2014