



Powering Business Worldwide

pe.eaton.com

DOE 2016 Efficient Transformer, Dry-type, Ventilated, Three- phase

V48M22T7516

UPC:786680175701

Dimensions:

- **Height:** 43 IN
- **Length:** 24 IN
- **Width:** 30.5 IN

Weight:1.1 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Coil Material:** Aluminum
- **Efficiency:** DOE2016
- **Enclosure:** NEMA 2
- **Frame:** 942
- **Frequency Rating:** 60 Hz
- **Insulation:** 220C
- **Kva Rating:** 75 kVA
- **Material:** Al windings
- **Phase:** Three-phase
- **Primary Voltage:** 480V Delta
- **Secondary Voltage:** 240V w/120V tap
- **Sound Level:** NEMA ST-20
- **Tap Size:** +2,-4 at 2.5%
- **Temperature Rating:** 150°C rise
- **Weathershield:** WS59
- **Wiring Connection:** 282B

Supporting documents:



- [Eaton Specification Sheet - V48M22T7516](#)

Certifications: No Data

Product compliance: No Data

© 2016 Eaton. All rights reserved.