

DRAWING NO. 30009514		7			6			5			4		3		2		1						
CATALOG NO.		ITEM NO.	STUD SIZE	CU. CONDUCTOR RANGE	INSULATION COLOR	INSULATION TYPE	L	C	Z	Y	INSTALLATION TOOLING	WIRE STRIP LENGTH	FIG NO.										
D	TI6-6LF	30013263	4-6	22 AWG - 18 AWG	RED	BARE	.83 [21]	.25 [6]	.32 [8]	.54 [14]	MRE1022B, MR8G98, Y8MRB-1, MR20, Y10D, Y10-22	9/32"	I										
	TI6-8LF	30013264	6-8	22 AWG - 18 AWG	RED	BARE	.83 [21]	.31 [8]	.32 [8]	.57 [15]			I										
	TI6-10LF	30013265	8-10	22 AWG - 18 AWG	RED	BARE	.83 [21]	.31 [8]	.32 [8]	.63 [16]			I										
	TI4-6LF	30013266	4-6	16 AWG - 14 AWG	BLUE	BARE	.81 [21]	.25 [6]	.30 [8]	.54 [14]			I										
	TI4-8LF	30013267	6-8	16 AWG - 14 AWG	BLUE	BARE	.83 [21]	.30 [8]	.30 [8]	.57 [15]			I										
	TI4-10LF	30014773	8-10	16 AWG - 14 AWG	BLUE	BARE	.83 [21]	.32 [8]	.30 [8]	.63 [16]			I										
	TI0-6LF	30013268	4-6	12 AWG - 10 AWG	YELLOW	BARE	.90 [23]	.30 [8]	.29 [8]	.54 [14]		11/32"	I										
	TI0-8LF	30013269	6-8	12 AWG - 10 AWG	YELLOW	BARE	.90 [23]	.33 [8]	.29 [8]	.57 [15]			I										
	TI0-10LF	30013270	8-10	12 AWG - 10 AWG	YELLOW	BARE	.90 [23]	.35 [9]	.29 [8]	.63 [16]			I										
C	TN18-6LF	30008919	4-6	22 AWG - 18 AWG	RED	MOLDED NYLON	.95 [24]	.25 [6]	.32 [8]	.66 [17]	MRE1022NV, MR8-83, Y10D, Y10-22	7/32"	2										
	TN18-8LF	30008920	6-8	22 AWG - 18 AWG	RED	MOLDED NYLON	.95 [24]	.31 [8]	.32 [8]	.69 [18]			2										
	TN18-10LF	30008921	8-10	22 AWG - 18 AWG	RED	MOLDED NYLON	.95 [24]	.31 [8]	.32 [8]	.75 [19]			2										
	TN14-6LF	30008922	4-6	16 AWG - 14 AWG	BLUE	MOLDED NYLON	.93 [24]	.25 [6]	.30 [8]	.66 [17]			2										
	TN14-8LF	30008923	6-8	16 AWG - 14 AWG	BLUE	MOLDED NYLON	.95 [24]	.30 [8]	.30 [8]	.69 [18]			2										
	TN14-10LF	30008924	8-10	16 AWG - 14 AWG	BLUE	MOLDED NYLON	.95 [24]	.32 [8]	.30 [8]	.75 [19]			2										
	TN10-6LF	30008925	4-6	12 AWG - 10 AWG	YELLOW	MOLDED NYLON	1.02 [26]	.30 [8]	.29 [8]	.66 [17]		11/32"	2										
	TN10-8LF	30008926	6-8	12 AWG - 10 AWG	YELLOW	MOLDED NYLON	1.02 [26]	.33 [8]	.29 [8]	.69 [18]			2										
	TN10-10LF	30008927	8-10	12 AWG - 10 AWG	YELLOW	MOLDED NYLON	1.02 [26]	.35 [9]	.29 [8]	.75 [19]			2										
B	YAE18N104LFBOX	30008928	4-6	22 AWG - 18 AWG	RED	3 PC NYLON	.95 [24]	.25 [6]	.32 [8]	.66 [17]	MRE1022NV, MR8-83, Y10D, Y10-22	7/32"	3										
	YAE18N105LFBOX	30008929	6-8	22 AWG - 18 AWG	RED	3 PC NYLON	.95 [24]	.31 [8]	.32 [8]	.69 [18]			3										
	YAE18N106LFBOX	30008930	8-10	22 AWG - 18 AWG	RED	3 PC NYLON	.95 [24]	.31 [8]	.32 [8]	.75 [19]			3										
	YAE14N107LFBOX	30008931	4-6	16 AWG - 14 AWG	BLUE	3 PC NYLON	.93 [24]	.25 [6]	.30 [8]	.66 [17]			3										
	YAE14N108LFBOX	30008932	6-8	16 AWG - 14 AWG	BLUE	3 PC NYLON	.95 [24]	.30 [8]	.30 [8]	.69 [18]			3										
	YAE14N109LFBOX	30008933	8-10	16 AWG - 14 AWG	BLUE	3 PC NYLON	.95 [24]	.32 [8]	.30 [8]	.75 [19]			3										
	YAE10N110LFBOX	30008934	4-6	12 AWG - 10 AWG	YELLOW	3 PC NYLON	1.02 [26]	.30 [8]	.29 [8]	.81 [21]		11/32"	3										
	YAE10N111LFBOX	30008935	6-8	12 AWG - 10 AWG	YELLOW	3 PC NYLON	1.02 [26]	.33 [8]	.29 [8]	.81 [21]			3										
	YAE10N112LFBOX	30008936	8-10	12 AWG - 10 AWG	YELLOW	3 PC NYLON	1.02 [26]	.35 [9]	.29 [8]	.87 [22]			3										
A	YHSA18K6LF	30008937	4-6	22 AWG - 18 AWG	RED	HEAT SHRINK	1.20 [31]	.25 [6]	.32 [8]	.66 [17]	MR22	7/32"	4										
	YHSA18K8LF	30008938	6-8	22 AWG - 18 AWG	RED	HEAT SHRINK	1.20 [31]	.31 [8]	.32 [8]	.69 [18]			4										
	YHSA18K10LF	30008939	8-10	22 AWG - 18 AWG	RED	HEAT SHRINK	1.20 [31]	.31 [8]	.32 [8]	.75 [19]			4										
	YHSA14K6LF	30008940	4-6	16 AWG - 14 AWG	BLUE	HEAT SHRINK	1.18 [30]	.25 [6]	.30 [8]	.66 [17]			4										
	YHSA14K8LF	30008941	6-8	16 AWG - 14 AWG	BLUE	HEAT SHRINK	1.20 [31]	.30 [8]	.30 [8]	.69 [18]			4										
	YHSA14K10LF	30008942	8-10	16 AWG - 14 AWG	BLUE	HEAT SHRINK	1.20 [31]	.32 [8]	.30 [8]	.75 [19]			4										
	YHSA10K6LF	30008943	4-6	12 AWG - 10 AWG	YELLOW	HEAT SHRINK	1.27 [32]	.30 [8]	.29 [8]	.81 [21]		11/32"	4										
	YHSA10K8LF	30008944	6-8	12 AWG - 10 AWG	YELLOW	HEAT SHRINK	1.27 [32]	.33 [8]	.29 [8]	.81 [21]			4										
	YHSA10K10LF	30008945	8-10	12 AWG - 10 AWG	YELLOW	HEAT SHRINK	1.27 [32]	.35 [9]	.29 [8]	.87 [22]			4										

FIG. 1

FIG. 2

FIG. 3

FIG. 4

NOTE:

1. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS
 ROUNDED OFF TO THE NEAREST MILLIMETER,
 UNLESS OTHERWISE NOTED, AND ARE FOR REFERENCE ONLY.

TO ORDER BURNDY® PRODUCTS CALL

UNITED STATES
1-800-346-4175 (LONDONDERRY, NH)

CANADA:
1-800-361-6975 (QUEBEC)
1-800-387-6487 (ALL OTHER PROVINCES)

FOR PRODUCT INFO: <http://www.burndy.com>

SNAP FORK TONGUE

ITEM NO: 30008937

CAT. NO: SEE TABLE

DRAWN BY: N.D.KANNAN 12/13/2010

CHECKER: K.BOUTIN 03/08/2011

DSN APPVL: K.BOUTIN 03/08/2011

MFG APPVL: P.KEENAN 03/08/2011

QA APPVL: C.KOWALCZYK03/10/2011

MKT APPVL: J.SYLVA 03/09/2011

PROD FAM: CM&R COMPRESSION

PROJECT #: --

DOCUMENT TYPE: Sales

REL LEVEL: Released

SCALE: 3:1

DRAWING NO 30009514

SHEET 1 OF 1

REV B