



# **SmartMate**

## SMARTMATE ICN3TTP40SC35M

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

#### **Product data**

| General Information           |                        | Wiring                                 |                     |
|-------------------------------|------------------------|--|---------------------|
| Lamp Type                     | FT40W/2G11             | Color Input Terminals                  | No terminals        |
| Number of Lamps               | 2/3 piece/unit         | Color Output Terminals                 | No terminals        |
| Ballast Type                  | Electronic Fluorescent | Wire Striplength                       | 0.50/0.375 mm       |
| Base Model                    | ICN3TTP40SC            | Lamp Connection                        | Parallel            |
| Suitable For Outdoor Use      | Yes                    | Wire Length by Color                   | See data sheet      |
| Automatic Restart             | Yes                    | Wire Gauge (Nom)                       | 18AWG mm            |
|                               |                        | Wire Type                              | Solid               |
| Operating and Electrical      |                        | Remote Wiring Configuration Allowed    | Yes                 |
| Input Voltage                 | 120 to 277 V           | Tandem Wiring Configuration Allowed    | Yes                 |
| Input Frequency               | 50 to 60 Hz            | Through Wiring Configuration Allowed   | Yes                 |
| Total Harmonic Distortion USA | 10 %                   | Max Ballast-Lamp Distance Remote Wirl  | ng 20'              |
| Ignition Method               | Instant Start          | Max Ballast-Lamp Distance Tandem Wiri  | <b>ng</b> Any = 20' |
| Crestfactor (Nom)             | 1.7                    | Max Ballast-Lamp Distance Through Wiri | <b>ng</b> Any = 20' |
| Ignition Time (Nom)           | 0.1 s                  | Connector Type                         | No connector        |
| Ballast Factor (Nom)          | 0.88                   |  |                     |
| Power Factor (Nom)            | 0.98                   | Temperature                            |                     |
| Input Current (Max)           | 0.83 A                 | T-Case Maximum (Nom)                   | 70 °C               |
| Input Current (Min)           | 0.35 A                 |  |                     |
| Input Power (Nom)             | 99-97 W                | Mechanical and Housing                 |                     |
| Rated Lamp Power              | 40 W                   | Housing Material                       | Metal               |
|                               |                        | Housing                                | SC                  |
|                               |                        |  |                     |

### SmartMate

| Housing Dimensions       | 9.5" x 1.7" x 1.18"                            |  |  |  |
|--------------------------|--|--|--|--|
|                          |  |  |  |  |
| Approval and Application |  |  |  |  |
| EMC Immunity Standard    | FCC Non-Consumer                               |  |  |  |
| Approval Marks           | CSA certificate UL certificate CEC Listing RoH |  |  |  |
|                          | Compliant                                      |  |  |  |
| Hum And Noise Level      | A  |  |  |  |
| UL Recognized            | No   |  |  |  |
|                          |  |  |  |  |
| Product Data             |  |  |  |  |
| Order product name       | SMARTMATE ICN3TTP40SC35M                       |  |  |  |

| EAN/UPC - Product               | 781087065105 |  |  |
|---------------------------------|--------------|--|--|
| Order code                      | 913710835402 |  |  |
| Numerator - Quantity Per Pack   | 1            |  |  |
| Numerator - Packs per outer box | 20           |  |  |
| Material Nr. (12NC)             | 913710835402 |  |  |
| Net Weight (Piece)              | 0.577 kg     |  |  |
|                                 |              |  |  |

#### **Dimensional drawing**



| Product                  | A1     | A2      | B1     | C1      |
|--------------------------|--------|---------|--------|---------|
| SMARTMATE ICN3TTP40SC35M | 9.5 in | 8.90 in | 1.7 in | 1.18 in |





© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2018, March 19 - data subject to change