



NOTES:

1. TERMINATED WITH (8 POSITION) UTP MODULAR PLUGS ON BOTH ENDS PER T568B.
2. CONSTRUCTED WITH 4-PR/26AWG STRANDED F/UTP CAT6A PATCH CABLE
3. MATERIAL:
PLUG: POLYCARBONATE
BOOT: THERMOPLASTIC RESIN
4. FLAMMABILITY RATING: CM/LSZH DUAL RATED

T568B WIRING SCHEME

PLUG POSITION:	CABLE WIRE:
1	WHITE/ORANGE
2	ORANGE
3	WHITE/GREEN
4	BLUE
5	WHITE/BLUE
6	GREEN
7	WHITE/BROWN
8	BROWN

CABLE COLORS	** = COLOR
OFF WHITE	--
BLACK	BL
BLUE	BU
RED	RD
YELLOW	YL
GREEN	GR
GRAY	GY

PANDUIT PART NUMBER	MIN. CABLE LENGTH
NK6APC3**	3 FT
NK6APC5**	5 FT
NK6APC7**	7 FT
NK6APC10**	10 FT
NK6APC14**	14 FT
NK6APC20**	20 FT
NK6APC1M**	1 METER
NK6APC2M**	2 METERS
NK6APC3M**	3 METERS
NK6APC4M**	4 METERS
NK6APC5M**	5 METERS
NK6APC7M**	7 METERS
NK6APC10M**	10 METERS
NK6APC15M**	15 METERS

PART NUMBER		NK6APCXX**	
TITLE			
NETKEY CATEGORY 6A UTP PATCH CORD			
CUSTOMER DRAWING			
ITEM REVISION NAME		14M504BB/00	
DATASET FILE NAME		14M504BB_DC02/00A	
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm)		MATERIAL:	
.X ± .03 (.8)		SEE NOTE 3	
.xxx ± .010 (.3)		DRAWING NUMBER:	
ANGLES ±		14M504BB-02	
THIRD ANGLE PROJECTION		SHT 1 OF 1	
DRAWN BY	DATE	CHK	SCALE
BJN	10-21-14	SCAL	NONE
REV			SIZE
DESCRIPTION			A

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
R	10-21-14	BJN	SCAL	LPH	RELEASED TO PRODUCTION	14M504BB-02

