

Rittal – The System.

Faster – better – everywhere.

Connection Adapters – SV 9342.240

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Connection Adapters – SV 9342.240

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Cover: ABS Chassis: Polyamide (PA 6.6) Chassis 3439.010: Fiberglass-reinforced, thermoplastic polyester (PBT) Fire protection corresponding to UL 94-V0 Chassis: Polyamide (PA 6.6)
Color:	RAL 7035
Note:	The technical data may vary for UL applications. UL approval only applies in conjunction with AC application The rated operating voltage for DC applications depends on the busbar arrangement in the busbar support 9340.050/9341.050/9342.050.

Product features

Suitable for busbars:	with cross-section height: 5 mm (0.2 ") with cross-section height: 10 mm (0.39 ")
Number of poles:	3-pole
For bar systems with center-to-center spacing:	60 mm
Dimensions:	Height: 210 mm (8.3 ") Width: 55 mm (2.2 ")
Rated operating voltage:	690 V, 3~
Clamping area for laminated copper	Height: 7.8 mm Width: 10 mm (0.39 ")

bars::

Connection for round conductor cross-sections:	Fine wire with wire end ferrule: 10 mm ² - 25 mm ² Multi-wire: 16 mm ² - 35 mm ²
Rated current (max.):	125 A
Cable outlet:	Bottom
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.38 kg (0.8 lb.)
EAN:	4028177522947
Customs tariff number:	85369010
ETIM 6.0:	EC001531
ETIM 5.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 7.0/7.1:	27370304
eCl@ss 6.0/6.1:	27370304
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Connection adaptor, 125 A, 690 V, 3-pole, cable outlet bottom, round conductor connection 10-35 mm ² , clamping area WH: 10x7,8 mm

Approvals

Approvals:	ABS C-UL DNV-GL UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity