


Hardware and Rough-In Products

Grounding Screws for Metal Boxes

- Color-coded green
- Size 10-32 x 3/8, fits tapped screw hole in most boxes
- Cat. No. 11-104 taps its own threads



CAT. NO.	DESCRIPTION	STD. CTN.
11-101	Washer Head Screws	1,000
11-104	Hex/Phillips/Slotted Head Self-Tapping	1,000

Anchors — Metallic

Lead Expansion Anchors


- For heavy-duty anchoring in solid masonry
- One setting tool supplied in each standard carton; no screws supplied



CAT. NO.	SCREW SIZE	HOLE DEPTH (IN.)	DRILL SIZE	STD. CTN.
53-308	1/4-20	7/8	1/2	500
53312	3/8-16	1 1/4	3/4	250

Mushroom Head Toggle Bolts

- "Spring-Wing" type, zinc plated
- Bolts are threaded full length



CAT. NO.	SIZE	DRILL HOLE (IN.)	STD. CTN.
52-602	1/8 (6-32) x 3	3/8	250
52-604	1/8 (6-32) x 4	3/8	250
52-622	3/16 (10-24) x 3	9/16	250
52-624	3/16 (10-24) x 4	9/16	250
52-632	1/4-20 x 3	3/4	250
52-634	1/4-20 x 4	3/4	250

Anchors — Non-Metallic

Economy Plastic Screw Anchor

- Superior holding power in solid masonry or concrete block



CAT. NO.	SIZE	FOR TAPPING SCREWS		DRILL* HOLE (IN.)	STD. CTN.
		SIZE	LENGTH (IN.)		
50-404	#12 x 1"	10 to 12	1	1/4	1,000

* When impact hammer drill is used, downsize drill hole 1/32".

Economy Screw Anchor Kits



CAT. NO.	DESCRIPTION	STD. CTN.
51-404*	(100) #12 x 1" Screw Anchor (100) 10 x 1" Slot/Phillips Head Screws (1) 1/4" Carbide-Tip Drill Bit	12
51-404HX	(100) #12 x 1" Screw Anchor (100) 10 x 1" Hex-Slotted Screws (1) 1/4" Carbide-Tip Drill Bit	12

* Now with Slot/Phillips screws.