

Rittal – The System.

Faster – better – everywhere.

TopTherm Filter Fan Units EMC – SK 3243.610

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm Filter Fan Units EMC – SK 3243.610

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Color: RAL 7035

**Protection category
IP to IEC 60 529:** IP 56
with standard filter and hose-proof hood: IP 56

Supply includes: Complete unit ready for connection, including filter mat

Note: For energy-efficient operation of the filter fan units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat.

Product features

**Air throughput
(unimpeded air flow):** At 50 Hz: 550 m³/h (323.7 cfm)
At 60 Hz: 600 m³/h (353.1 cfm)

**Rated operating
voltage:** 115 V, 1~, 50 Hz/60 Hz

Dimensions: Height: 323 mm (13 ")
Width: 323 mm (13 ")

**Required mounting
cut-out:** Height: 292 mm (11 ")
Width: 292 mm (11 ")

Build depth: 25 mm (0.98 ")

Installation depth: 118.5 mm (4.7 ")

Temperature range:	Storage: -30°C...+70°C Operation (environment): -30°C...+55°C
EMC version:	yes
Rated power Pel:	At 50 Hz: 75 W At 60 Hz: 90 W
Rated current (max.):	At 50 Hz: 0.78 A At 60 Hz: 0.8 A
Miniature circuit-breaker/fuse:	6 A
Noise pressure level:	At 50 Hz: 59 dB(A) At 60 Hz: 61 dB(A)
Diagonal fan:	Axial, self-starting shaded pole motor
Packaging unit:	1 pc(s).
Weight/packaging unit:	3.56 kg (7.8 lb.)
EAN:	85949
Customs tariff number:	84145100
Approvals	
Approvals:	DNV-GL UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity