

Industrial Specification Grade Straight Blade Receptacles

2-Pole, 3-Wire Grounding
15A, 125V/AC
20A, 125V/AC
NEMA 5-15R, 5-20R




5-15R




5-20R

Industrial Grade Receptacles


Back Wire & Side Wire	15A, 125V NEMA 5-15R	UL FUL S SF NOM 426	20A, 125V NEMA 5-20R	UL FUL S SF NOM 426
Description	Catalog No. Color Suffix		Catalog No. Color Suffix	
Back & Side Wire Duplex Receptacle	□ 5252 A, B, BK, BL, GY, LA, RD, V, W	•	□ 5352 A, B, BK, BL, GY, LA, RD, V, W	•
Side Wire Duplex Receptacle	□ 5242 B, BK, GY, V, W		□ 5342 B, BK, GY, V, W	
Side Wire Single Receptacle	□ 5251 B, LA, RD, V	•	□ 5351 B, BK, RD	•




5252



5352_M



5351



6342

Decorator Industrial Grade Receptacle

Side Wire	20A, 125V; NEMA 5-20R	UL FUL S SF NOM 426
Description	Catalog No. Color Suffix	
Decorator Duplex Receptacle	□ 6342 A, LA, V, W	•

Color Ordering Information

For ordering receptacles, include Cat. No. followed by the color code: A (Almond), B (Brown), BK (Black), BL (Blue), GY (Gray), LA (Light Almond), RD (Red), RN (Orange), V (Ivory), W (White)

Icon Key

➡ ArrowLink™ option available. Add "M" suffix to Standard catalog number (example 5252RD, 5252RDM). For ordering information on ArrowLink & ArrowLink SPD connectors, see page A-3.



Build-To-Spec Customizable Devices - see page A-4



NAFTA Compliant - see page O-30

Accessories for Industrial Grade NEMA 5-15 & 5-20 Receptacles

Description	Catalog No.	
1-Gang standard size duplex receptacle stainless steel wallplate	□ 93101	•
1-Gang, stainless steel single receptacle stainless steel wallplate	□ 93091	•



93101



93091

Specification Information:

Duplex Industrial Receptacles: A-32

Decorator Industrial Receptacles: A-32

ArrowLink Industrial Receptacles: A-34

Single Industrial Receptacles: A-33

Commercial Specification Grade Receptacles

2-Pole, 3-Wire Grounding
15A, 125V/AC; 20A, 125V/AC
NEMA 5-15, 5-20

	Device Type	Commercial Grade Duplex and Decorator Duplex Receptacles: BR, CR, 6200, 6300, 6400 Series	Commercial Grade Single Receptacles: 800, 1800 Series	Snap-In Receptacles: 49, 67, 4049, 4067, 4070 Series
	Wiring Type	Back & side wire, except CR, 6250, 6350, 6450 series	Side wire	Wire leads & quick connect
	Testing & Code Compliance	cULus Listed to UL 498, file no. E15058	Listed to UL 498, file no. E15058	UR (UL Recognized)
		BR series only: UL verified to Federal Spec. WC-596G	CSA certified to 22.2, no 42, file no. 6914 (6233-01)	CSA certified to C22.2, no. 42, file no. 6914 (6233-01)
		CSA certified to 22.2, no 42, file no. 6914 (6233-01)	NOM/ANSI certified	NOM certified
		NOM/ANSI certified		
Specifications: Environmental	Flammability	Meets UL 94 requirements; V2 rated	Meets UL 94 requirements; V2 rated	Meets UL 94 requirements; V2 rated
	Temperature Rating	-20°C to 70°C (-4°F to 158°F)	-20°C to 70°C (-4°F to 158°F)	-20°C to 70°C (-4°F to 158°F)
Specifications: Electrical	Dielectric Voltage	Withstands 2000V per UL 498	Withstands 2000V per UL 498	Withstands 2000V per UL 498
	Current Interrupting	Yes, at full-rated current	Yes, at full-rated current	Yes, at full-rated current
	Temperature Rise	Max. 30°C (86°F) after 250 cycles of overload @ 200% of rated current (DC)	Max. 30°C (86°F) after 100 cycles of overload @ 150% of rated current (DC)	Max. 30°C (86°F) after 100 cycles of overload @ 150% of rated current (DC)
Specifications: Mechanical	Terminal Accommodation	#14 - 10 AWG	#14 - 10 AWG	#14 - 12 AWG
	Voltage Ratings	Permanently marked on device	Permanently marked on device	Permanently marked on device
Materials:	Face	Nylon	Nylon	Urea
	Base	PVC	Nylon	Polypropylene
	Strap	0.045" thick galvanized steel	0.040" thick galvanized steel	0.030" thick steel
	Auto Ground Clip	Phosphor bronze	0.032" brass	N/A
	Line Contacts	0.030" thick brass	0.030" thick brass	0.032" thick brass
	Ground Contact	Riveted	Riveted	Screw down
	Terminal Screws	Terminal: #8-32 brass, neutral screw nickel plated	Terminal: #8-32 brass, neutral screw nickel plated	N/A
	Ground Screw	Ground: #8-32 brass (green)	Ground: #8-32 brass (green)	Ground: #6-32 brass (green)